

10.24kwh 200AH Lithium Batterie Lifepo4 Rackmount Lithium Battery Energy **Storage System**

Basic Information

. Place of Origin: China Brand Name: **XWELL**

· Certification: UN38.3,MSDS,UL,CB,BIS,PSE,GB4943.1

safety standard, CE, FCC, ROHS, battery UN38.3, MSDS, UL, CB, BIS, PSE

XW-1024W-1 Model Number:

. Minimum Order Quantity: 1 pcs USD • Price: · Packaging Details: Carton

. Delivery Time: 7-10 working days

Payment Terms: L/C, D/A, D/P, T/T, Western Union,

MoneyGram

. Supply Ability: 5000 pcs per month



Product Specification

. Max Continuous Charge 200A

Curre:

10.24kwh Voltage(V):

LiFePO4 Prismatic Cell . Cell Type:

• Max Charge Current: 200A

• Discharge Cut-off Voltage: 42.5V-51.2V

 Communication Interface: RS485, RS232, CAN

Highlight: **Energy Storage System Rackmount Lithium**

, 200AH Rackmount Lithium Battery, 10.24kwh Rackmount Lithium Battery

Product Description

2.56kwh 50AH Lithium Batterie Lifepo4 All In One Home Energy Storage System

Rackmount Lithium Battery Energy Storage System

All-in-one home energy storage systems are self-contained, integrated units that combine battery storage, power conversion, and energy management capabilities into a single, compact solution for residential applications. These systems are designed to provide whole-home backup power and optimize energy usage.


Key Features

Integrated battery packs, inverter/charger, and control system
Typical storage capacity ranging from 8-20 kWh
Bidirectional inverter for grid-tied operation and backup power
Ability to interface with solar PV systems
Intelligent energy management software and mobile app integration
Automatic switchover to battery power during grid outages
Optimization of renewable energy usage and cost savings

Rackmount Lithium Battery Specification

Model	51.2V50Ah	51.2V100Ah	51.2V200Ah		
Nominal voltage	51.2V				
Nominal capacity (kwh)	2.56	5.12	10.24		
Cell type	LiFePO4				
Standard charge voltage	54.6V(adjustable)				
Max charge current	50A				
Discharge cut-off voltage	42.5V(adjustable)				
Max discharge current	50A				
Display	LCD(Optional)				
Communication interface	CAN/RS485/RS232				
Cycle life	>6000 Cycles (80%DOD)				
Charge temperature range	0~45°C				
Discharge temperature range	-20~60°C				
Color	Black				
Dimension (mm)	442x410x133 3U	442x410x177 4U	550x442x220 5U		
Weight	About 35Kg	About 42Kg	About 84Kg		
Installation method	Rack Mount				

Cell Specification of Rackmount Lithium Battery



#	Item	Parameter
A	Height	119±1.0 mm
В	Width	160±1.0 mm
С	Thickness	≤50 mm
D	Tabs Distance	97±0.5 mm

Operation Pannel of Rackmount Lithium Battery




#	Item	Function	#	Item	Function
(1)	Case Hanger	mount in 19 inch cabinet or anti-seismic rake	(8)	SOC Indicator	indicate battery capacity percentage
(2)	Handle	easy to handle, move and install	(9)	Dry Contact	remote on/off control by signal wires
(3)	Reset Switch	restart and wake up the battery	(0)	Comm. Port	RS485+RS232
(4)	On/Off Indicator	turn on/off green and indicate battery on/off	(11)	Comm. Port	RS232
(5)	Working Indicator	turn on green and indicate normal operation	(12)	Comm. Port	RS485+RS232
(6)	Alarm Indicator	turn on red when there is alarm or failure	(13)	Terminal Bar	charge and discharge terminal
(7)	DIP Switch	define battery IP for parallel connection	(4)	DC Switch	turn battery on/off

Size of Rackmount Lithium Battery



Structure of Rackmount Lithium Battery



#	Item	Material
(1)	Case Cover	SPCC
(2)	Case Hanger	SPCC
(3)	Insulation Sheet	Ethoxyline
(4)	Bus-Bar	Aluminum Alloy
(5)	Battery Cell	LFP, Aluminum Shel
(6)	Module Side Plate	ABS / PC
(7)	Cell Binding Loop	Plastic Steel
(8)	Case Bottom	SPCC
(9)	Insulating Wiring Terminal	Bakelite
(io)	Side Plate Combination Board	SPCC
(11)	BMS	PCB
(12)	Commination Board	PCB
(13)	DC Switch	1
(14)	Handle	Sherardized SPCC
(15)	Case Front Cover	SPCC
(16)	Terminal Bar (+ & -)	/

Application of Rackmount Lithium Battery

Application Scenario



Data Center



C&I Park



Telecom Base



Medical Equipment

Why choose us?

We production of battery products are widely used in communications, power, financial systems, uninterruptible power supply systems (UPS), power plant and substation switch control, solar panels, controllers inverter etc solar systems, emergency lighting, alarm systems, cars, ships, motorcycles, electric bicycles and other industries. Sales network covers all provinces, municipalities, autonomous regions and established offices in various places and aftersales service center.

Our team with Yuasa ,BYD battery senior consultant,High quality technical management team, advanced production and testing equipment to ensure the quality of the battery is reliable.



XWELL GUANGDONG XWELL TECHNOLOGY CO., LTD.



+86 18620492985



sales@esslithiumbattery.com



esslithiumbattery.com